

Controlled Air Design
(800) 635-0298
controlledairdesign.com



CONTROLLED
AIR DESIGN
controlledairdesign.com



Applicable Requirements :

ANSI/UL 1017

CSA C22.2 No.243



Complies with NFPA 77 "Recommended Practice on Static Electricity"



Characteristics



Stainless
General



SD Accessories
- Included



HEPA -
Included



High Filtration
Efficiency Unit



Dry Recovery



Brushless Motor
Available

- Ideal for housekeeping and general cleaning
- Complies with NFPA 652 paragraph 8.4.2.2.1.7 and NFPA 654 paragraph 8.4.3.7 (1) to (7)
- Protected against ingress of dust
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Heavy duty 2-stage by-pass motor
- Longer life brushless motor available. Always with 2 x H14 HEPA filters
- For dry recovery only
- Manual Filter Shaker (MFS) system
- Stainless steel tank SAE 430 fits any application
- Filter blockage indicator light
- Includes a complete static dissipative tool kit

Specifications

2D-25L (DT) MFS HEPA ORDLOC-652	111405A
Model Name	2D-25L (DT) MFS HEPA ORDLOC-652
Type (Powerhead)	Electric
Voltage	120 V
Hertz	60 Hz
Phase	Single
Wattage	1200 W
Power	1.6 HP
Amperage	10.5 A
Air Flow	110 CFM
Vacuum Pressure	107 " H ₂ O
Sound Level	75 dB(A)
Plug Type	120V
Suction Inlet	60 mm
Cart Type	Detachable Tank (DT)
Filter Cleaning	Manual Filter Shaker (MFS)
Dry Recovery - Tank	6.6 Gal
Cord Length	35 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Longer Life Brushless Motor Available (always with 2 x H14 HEPA filters)