

Controlled Air Design
(800) 635-0298
controlledairdesign.com



Applicable Requirements :
ANSI/UL 1017
CSA C22.2 No.243
Complies with NFPA 77 "Recommended Practice on Static Electricity"



Characteristics



- Complies with NFPA 652 paragraph 8.4.2.2.1.7 and NFPA 654 paragraph 8.4.3.7 (1) to (7)
- Protected against ingress of dust
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- For general housekeeping
- Dual bypass/dual speed heavy duty motors. 2000W (2400 max.)
- Manual Filter Shaker (MFS) system
- For dry recovery only
- Stainless steel SAE 430 body and recovery tank
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Includes a complete static dissipative tool kit
- Brushless motor available

Specifications

4D-55L (DT) MFS HEPA ORDLOC-652	112111A
Model Name	4D-55L (DT) MFS HEPA ORDLOC-652
Type (Powerhead)	Electric
Voltage	120 V
Hertz	60 Hz
Phase	Single
Wattage	2040 W
Power	2.7 HP
Amperage	15.2 A
Air Flow	200 CFM
Vacuum Pressure	90 " H ₂ O
Plug Type	20 Amps Explosion Proof
Suction Inlet	2 "
Cart Type	Detachable Tank (DT)
Filter Cleaning	Manual Filter Shaker (MFS)
Dry Recovery - Tank	14.5 Gal
Cord Length	33 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories