



Controlled Air Design - Raleigh, NC
(800) 635-0298
sales@controlledairdesign.com



BL 45
ATEX
Z22

Depureco Industrial Vacuums USA

19121 Marketplace Avenue, Building 1, Suite 165
Plum Creek Business Park • Kyle • TX 78640

www.depurecousa.com
info@depurecousa.com


2 HP
POWER

2325 in³
FILTER

11 gal
CAPACITY



Head with double stage filtration system.




BRUSHLESS MOTOR
120 V

PRESSURE GAUGE


Dirty filter indicator.



**M CLASS
ANTISTATIC
STAR FILTER**



**[OPTIONAL]
FILTER CARTRIDGE
HEPA H14**



**MANUAL SHAKER
CLEANING SYSTEM**

Smart handle for shaking the filter aggressively to release dust.

**INLET
WITH DEFLECTOR Ø 2 in**




**ALL COMPONENTS
ARE GROUNDED**


**STAINLESS STEEL BIN
AISI 304**

11gal

HIGHLY TRANSPORTABLE



21.65 in



24.41 in

51.29 in

Weight: 99 lbs

DETACHABLE BIN



NFPA 660 Compliance



ATEX Marking:
II 3 D Ex htc III B T140°C Dc

SPEC SHEET

	Units	BL 45 ATEX Z22
Suction type		Brushless motor
Atex Marking		II 3 D Ex htc III B T284°F Dc
Power	HP	2 1 ~
Voltage Frequency	V/Hz	120 50
Maximum vacuum	inH2O	92
Maximum air flow	CFM	129
Inlet	Ø in	2.75
Noise level - (EN ISO 3744)	dB(A)	72
Bin capacity	gal	11
Dimensions	in	21.65 x 24.41
Height	in	51.29
Weight	lb	99
Primary filter		
Type		Star filter
Surface area	in² in	2325
(Class EN 60335-2-69)		M Class
Media		Antistatic polyester
Filter cleaning		Filter shaker
Absolute filter - Optional		
(Class - EN 1822)	in²	H14
Media		Fiberglass
In suction		Opt H14
In suction		E10
Engine air inlet cooling	in²	E10
Outgoing engine air cooling		E10

ACCESSORIES



ATEX STARTER KIT Ø 1.75 in



ATEX KIT PRO Ø 1.75 in

OPTIONAL



CYCLONIC SEPARATOR



Wet & Dry fixed brush floor tool