

NON-DIRECTIONAL AIR FLOW



NEW!

FX-180SF

Construction: High strength sewn single-ply PVC vinyl coated polyester fabric hose reinforced with a spring steel wire helix and external PVC wearstrip

Temperature Range: -20°F to 180°F

Size Range: 12" and 20"

Standard Color: White with White Wearstrip

Standard Length: 25'

- Sewn construction allows for better performance in lower and higher temperatures
- Specially designed construction that provides super air flow throughout vs. traditional sewn products
- Light weight duct designed for dehumidification applications
- Excellent compressibility created by less pronounced seams 10:1
- Wearstrip offers additional external abrasion and drag resistance
- Moisture resistant and UV stabilized to prevent mold and mildew
- Flame retardant to UL 94V-0
- Available with wire rope/nylon ring and enclosed belted cuff

DEHUMIDIFICATION



FX-180

Construction: High strength sewn single-ply PVC vinyl coated polyester fabric hose reinforced with a spring steel wire helix and external PVC wearstrip

Temperature Range: -20°F to 180°F

Size Range: 12" to 24"

Standard Color: Yellow with Black Wearstrip

Standard Length: 25 Feet

- Sewn construction allows for better performance in low and higher temperatures
- Light weight duct designed for dehumidification applications
- Great Compressibility 6:1
- Wearstrip offers additional external abrasion and drag resistance
- Moisture resistant and UV stabilized to prevent mold and mildew
- Flame retardant to UL 94V-0
- Also available in white with white wearstrip
- Available with wire rope/nylon ring and enclosed belted cuff

INDUSTRIAL RENTAL



FX-400

Construction: High strength sewn single-ply urethane coated polyester fabric hose reinforced with a spring steel wire helix and external PVC wearstrip

Temperature Range: -60°F to 400°F

Size Range: 12" to 24"

Standard Color: Black with Orange Wearstrip

Standard Length: 25 Feet

- Sewn construction allows for better performance in low and higher temperatures
- Light weight duct designed for portable and/or temporary heating
- Great Compressibility 6:1
- Safety orange wearstrip offers additional external abrasion and drag resistance
- Moisture resistant and UV stabilized to prevent mold and mildew
- Urethane coating increases puncture, abrasion and tear resistance
- Great chemical, fuel and oil resistance
- Flame retardant to ASTM D6413
- Ideal for commercial and residential work area heating, cement drying and event tents
- Available with wire rope/nylon ring and enclosed belted cuff

CONSTRUCTION / OIL & GAS



FX-550

Construction: High strength sewn single-ply heavy duty silicone coated fiberglass fabric hose reinforced with a spring steel wire helix and external wearstrip

Temperature Range: -50°F to 550°F

Size Range: 12" to 24"

Standard Color: Silver with Black Wearstrip

Standard Length: 25 Feet

- Sewn construction allows for better performance in low and higher temperatures
- Light weight duct designed for higher temperature portable and/or temporary heating and dehumidification applications
- Great Compressibility 6:1
- Flexible heater ducting able to withstand higher temperatures and maintain flexibility in cold weather conditions
- Wearstrip offers additional external abrasion and drag resistance
- Great puncture and tear resistance
- Flame retardant to UL 94V-0
- Available with wire rope/nylon ring and enclosed belted cuff
- Ideal heater duct for cold weather construction and oil and gas sites
- Combination ducting (FX-400 and FX-550) FX-Combo also available as an economical way to manage high heat